


## PRODUCT DESCRIPTION

With Dryvit™ woodgrain finish techniques, you can incorporate the look real woodgrain into your building's aesthetic — and also get the superior weatherability, durability and energy efficiency of a Dryvit Outsulation® system. Dryvit woodgrain textures are created with an application of Tibur Stone™ finish, and a coat of Demandit® Smooth. The wall is then sealed with Dryvit SealClear™. By varying degrees of pressure during application, installers can produce the exact amount of “knotting,” texture and grain depth desired for their specific project.

### STANDARD COLORS



ASH (870)



RED PINE (871)



DARK WALNUT (873)



SABLE (874)



BARK (875)



ESPRESSO (876)



SADDLE (877)



CEDAR (878)

All colors shown are approximate and may not reflect sheen or shade precisely, as varying amounts of aggregate will alter light-reflecting properties. The look achieved in this literature should be used as inspiration. The individual applicators' finish appearance will vary based on their interpretation of the application process. A mock-up is strongly encouraged to come to consensus on the woodgrain technique achieved.

Dryvit Systems, Inc. | One Energy Way | West Warwick, RI, 02893 | 401.822.4100 | [dryvit.com](http://dryvit.com)

Tremco Construction Products Group (CPG) brings together Tremco Incorporated's Commercial Sealants & Waterproofing and Roofing & Building Maintenance operating divisions; Dryvit Systems, Inc.; Nudura Inc.; Willseal; Weatherproofing Technologies, Inc. and Weatherproofing Technologies Canada, Inc.

Dryvit® and NewBrick® are registered trademarks of Dryvit Systems, Inc.  
Use of the © symbol indicates registration with the US Patent & Trademark Office and the Canadian Intellectual Property Office.

Part of  
 **TREMCO**  
Construction Products Group